



## De'Longhi 抽濕機特點 De'Longhi Dehumidifiers Features

### 呼吸一室清爽空氣

Breathe with a Smile

良好的濕度調控與居所的舒適密不可分。在季節轉換的時候，潮濕空氣會導致牆紙脫落、牆身或油漆剝落，以及使傢私變舊；而濕度更會引起發霉、有害細菌及霉味，長遠更可能導致種種健康問題。De'Longhi 不斷透過科研改良產品，設計出一系列耐用可靠的抽濕機，深受家庭信賴。

Optimal humidity level is one of the key criteria of a comfortable home. During changes of season, high levels of humidity can lead to the peeling or flaking of walls and deterioration of furniture; air condensation may cause growth of mould, harmful bacteria and unpleasant odor and in long term, may lead to various health problem. De'Longhi has designed and created a range of air-treatment appliances for the home with our constant dedication to research and experimentation, each air treatment product is a reliable and durable lifelong companion.



#### 五年壓縮器保用\* Five Years Compressor Warranty\*

各型號抽濕機的壓縮器均提供5年保用，首年更提供上門收機服務(離島及東涌除外)。Compressors of all models are provided with five years warranty. On-site pick-up service is available for first year (except Outlying Islands and Tung Chung).



#### 抽濕/放暖2合1\* 2 in 1 Dehumidifying /Heating\*

內置暖風機，抽濕放暖可同步進行，於既濕且凍的天氣下使用更為有效。With its built-in heater, it dehumidifies and heats at the same time, cutting the operating time in half. Combi function is useful in cool weather and in accelerating drying time.



#### 乾衣功能\* Laundry Dryer\*

乾衣模式以最大功率運行除濕功能，能更快烘乾衣物。The appliance operates at its maximum dehumidifying capacity. This mode allows laundry to dry quicker.



#### 高水位排水系統\* High Level Water Drainage System\*

內置壓力式排水系統，容許高水位排水，令抽濕不受空間及時間所限。(最高可達四米) Built-in pressure pump system allows high level of water drainage, which makes your home reaching the desired humidity level without any limitation of time or place. (Up to 4m)



#### 三種排水方式\* 3 Drainage Solutions\*

- 高水位排水系統
- 直接排水入水箱
- 連續由低水位排水 (不用水泵)
- High Level Water Drainage System
- Directly drain into its tank
- Continuously allow low water level of drainage (Without pump action)



#### 採用環保雪種 - R134a / R410a\* Use Ecological Gas - R134a / R410a\*

<http://www.delonghi.com/en-hk>

De'Longhi Kenwood A.P.A. Ltd  
客戶服務熱線 Customer Service Hotline

香港 Hong Kong +852 2237 1313  
澳門 Macau +853 2826 0302

De'Longhi Hong Kong

\* 上述功能分別適用於不同指定型號，詳情請參閱後頁圖表。

\* The above functions are available for different models separately. For more details, please refer to the comparison chart on the following page.

Breathe with  
a Smile  
呼吸一室清爽空氣

## 抽濕機 Dehumidifier



型號 Model	DD50P	DD30P	DDSE 25COMBI	DDSE20
抽濕模式 Dehumidifying Mode	壓縮器 Compressor	壓縮器 Compressor	壓縮器 Compressor	壓縮器 Compressor
能源標籤 Energy Label	3	2	2	1
抽濕量 - 能源標籤標準 (26.7°C / 60%相對濕度) MEELS Standard (26.7°C / 60% Relative Humidity)	30.52	19.02	14.13	14.78
抽濕量 - 製造商標準 (32°C / 80%相對濕度) Manufacturer's Standard (32°C / 80% Relative Humidity)	50	30	25	20
乾衣功能 Laundry Dry Function	-	-	√	√
抽濕溫度範圍 Dehumidifying Temperature Range	5-32	5-32	2-32	2-32
輸入功率 Input Power (W)	900	530	1200	410
送風 Air Distribution	單向 Direct	單向 Direct	單向 Direct	單向 Direct
風速選擇 Fan Speed	2	2	3	3
過濾特性 Filter Features	可清洗過濾網 Washable Dust Filter	可清洗過濾網 Washable Dust Filter	可清洗過濾網 Washable Dust Filter	可清洗抗菌過濾網 Washable Anti-bacterial Filter
控制面板 Control Panel	電子控制 Electronic	電子控制 Electronic	電子控制 Electronic	電子控制 Electronic
防溢裝置 Tank Control System	√	√	√	√
運作水箱容量(公升) Tank Capacity - Operation (L)	6	6	4.5	4.5
手挽式水箱 Water Tank with Handle	√	√	√	√
連續抽濕安全系統 Continuous Draining Safety System	√	√	√	√
滑輪 Castors	√	√	√	√
手柄 Handles	√	√	√	√
環保雪種 Ecological Refrigerant Gas	R410a	R410a	R134a	R134a
操作寧靜(最大分貝) Noise Level (dB) Max.	55	53	50	50
強力排水系統 Heavy Duty Pump System	√	√	-	-
電子防結霜裝置 Electronic Anti-Frost Device	√	√	√	√
24小時時間掣 24-Hour Timer	√	√	√	√
體積(高x闊x深)毫米 Dimension (HxWxD) mm	616 x 390 x 320	616 x 390 x 320	488 x 346 x 278	488 x 346 x 278
重量(公斤) Weight (Kg)	18.1	16.3	15	15

產品圖片僅供參考。 Product photos are for reference purpose only.  
產品設計及規格如有更改，恕不另行通知。 Design and specifications are subject to change without prior notice.

**DeLonghi**  
Better Everyday

Breathe with  
a **Smile**  
呼吸一室清爽空氣

抽濕機系列  
Dehumidifier Collection

